

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BPM347-04A1	345.825~ 349.425	3.0	14.0	5 @ Fc±3.5 30 @ 397.6~445.6 5 @ 3102.3~3152.3	45 x 23 x 16.3
BPM382-05A1	380~385	3.0	15.0	40 @ 390~395	47 x 28.7 x 15.3
BPM392-05A1	390~395	3.0	15.0	40 @ 380~385	47 x 27.9 x 15.3
BPM425-30A1	410~440	1.5	14.0	50 @ 480	28.5x17.5x9.5
BPM447-04A1	445.825~ 449.425	3.0	15.0	5 @ Fc±3.5 MHz 30 @ 349.625~397.625 5 @ 3102.375~3152.375 20 @ 10 MHz	45 x 23 x 16.3
BNM450-06A1	462~468	1.8	10	40 @ 375 40 @ 555~600	14.6 x 16.4 x 5.81
BPM495-30A1	480~510	1.5	14.0	50 @ 440	28.5x17.5x9.5
BPM625-125A1	562.5~687.5	2.0@Fc	12.0	50 @ DC~437.5, 50@812.5~4000	50.0x17.0x8.0
BPM707-06A1	704~710	2.5	15.0	30 @ 607, 807	8.4 x 10.4 x 3.9
BNM707-15A1	699.5~714.5	2.5	1.7:1	38 @662, 35 @ 752	24 x 11.9 x 6
BPM707-18A1	698~716	3.0	15	25 @ 728	40.5x15.0x8.2
BPM707-18B1	698~716	3.0	15	50 @ 728~746	44.0x20.5x9.5
BCM720-20A1	710 ~ 730	3.0	18	80 min @ 580, 65 min @ 650 60 min @ 790	60.0 x 40.0 x 20.0
BCM720-400A1	520 ~ 920	2.0	20	35 min @ 325, 35 min @ 1310	50.0 x 30.0 x 15.0
BPM721-60A1	691~751	2.5	15.0	30 @ < 671 30 @ 771~1000	40.5 x 10 x 8
BNM725-45A1	703~748	2.5	15.0	20 @ 758~803	29.2x15.7x4.8
BPM725-45A1	703~748	4.0	14.0	25 @ 758~803	42.5x17.5x9.5
BPX725-45A1	703~748	3.5	15.0	17 @ 758~803	19.1x19.1x5.1
BNM726-15A1	718.5~733.5	2.5	1.7:1	38 @681, 35 @ 771	24 x 11.9 x 6
BPM726-27A1	713~740	3.0	18.0	40 @ 768~795, 700	28.0x23.0x9.5
BPM726-27B1	713~740	3.0	18.0	40 @ 768~795, 700	63.5x40.6x25.4
BPM737-18A1	728~746	3.5	15	40 @ 716, 758	42.0x19.0x8.8
BPM737-18B1	728~746	3.0	15	50 @ 698~716	44.0x20.5x9.5

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BPM751-10A1	746~756	3.5	14.0	55 @ 777~787	35.0x20.0x9.5
BPM751-11A1	746~757	3.0	15.0	50 @ 776~787	44.0x20.5x9.5
BPM763-10A1	758~768	2.5	15.0	50 @ 788~798	28.0x20.0x9.5
BPM769-12A1	763~775	2.0	13.0	50 @ 793	42.0x17.0x9.5
BPM769-14A1	762~776	2.0	15.0	32 @ 792~824 40 @ 824~900, < 700	24.8 x 9.5 x 8.2
BNM770-12A1	764~776	2.0	2.0:1	15 @ 741, 40 @ 706	11.6 x 10.3 x 3.9
BPM772-6A1	769~775	5.0	13.0	60@798	42.0x17.0x9.5
BNM777-15A1	763.5~778.5	2.5	1.7:1	38 @ 681, 35 @ 771	24 x 11.9 x 6
BPM780-45A1	758~803	2.5	15.0	60 @ 703~748	70.0x24.0x17.0
BPM781-11A1	776~787	3.0	15.0	50 @ 746~757	44.0x20.5x9.5
BPM781-11A1	776~787	3.0	15.0	50 @ 746~757	44.0x20.5x9.5
BPM781-27A1	768~795	1.0	18	20 @ 713~740	20.0x22.0x10.5
BNM782-10A1	777~787	2.5	15.0	35 @ 746~756	12.7x12.7x2.54
BPM782-10A1	777~787	2.5	14.0	35 @ 746~756	35.0x20.0x9.5
BNM793-10A1	788~798	2.5	15.0	35 @ 758~768	12.7x12.7x2.54
BPM793-10A1	788~798	2.5	15.0	25 @DC~768, 818~1600 50@758~768	28.0x20.0x9.5
BNM800-12A1	794~806	2.0	2.0:1	15 @ 771, 40 @ 736	11.6 x 10.3 x 3.9
BPM808-32A1	792~824	2.0	15.0	40 @ 762~776, 851~894 40 @ < 762, 894	40.5 x 13.7 x 8
BPM813-19A1	823~842	3.5	10	15 @ 849~868	10.08 x 8.69 x 4.2
BPM815-18A1	806~824	2.3	15.0	35 @ DC~740 25 @ 850, 10 @837.5	13.5 x 9 x 6.2
BPM815-18B1	806~824	2.0	14.0	35 @ DC~740 25 @ 850	13.75 x 13.5 x 6
BPM815-18C1	806~824	3.0	15.0	60 @ 851~869	44.0x20.5x9.5
BNM815-19A	806~825	3.0	2.0:1	30 @ 851	15 x 9.1 x 3.8
BPM823-02A1	822~824.5	2.0	11.0	50 @ Fo+90, 30 @ Fo-90	10.08 x 8.69 x 4.2

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BPM824-02A1	823~825	2.5	2.0	17 @ 799, 849	10.08 x 8.69 x 4.2
BPM824-06A1	821~827	2.0	2.0:1	40 @ 914 35 @ 734	12 x 9.3 x 6.1
BPM836-15A1	829~844	3.5	10.0	15 @ 869~894	8.3 x 9 x 4
BPM836-25D1	824~849	2.0	1.5:1	38 @ Fc±80 43 @ Fc±100	13 x 12 x 4.7
BNM836-25A1	824~849	3.0	2.0:1	18 @ 804 12 @ 869	11.4 x 8.5 x 3.9
BNM836-25B1	824~849	3.0	2.0:1	18 @ 804 30 @ 869	14 x 11 x 4.2
BPM836-25A1	824~849	2.3	15.0	35 @ DC~700, 25 @ 869~1500	13.5 x 8.8 x 6.2
BPM836-25B1	824~849	2.0	1.5:1	25 @ Fo±32.5	19 x 17 x 7
BPM836-25C1	824~849	4.0	1.5:1	40 @ 780, 869	32 x 17 x 4.7
BPM836-25E1	824~849	3.0	18	60 @ 869~894, 40@859	44.0x20.5x9.5
BPM857-115A1	800~915	2.0	15.0	40 @ 680, 15 @ 756 15 @ 950, 40 @ 1035	32.4 x 13.4 x 8
BPM858-19A1	849~868	3.5	10.0	20 @ 804~823	8.3 x 8.8 x 4
BPM860-18A1	851~869	2.3	15.0	25 @ DC~824 35 @ 940, 10 @ 837.5	13.5 x 13 x 6.2
BPM860-18B1	851~869	2.0	14.0	25 @ DC~824 35 @ 940	13.5 x 13 x 6
BPM860-18C1	851~869	3.0	15.0	60 @ 806~824	44.0x20.5x9.5
BPM860-20A1	850~870	2.0	15.0	32 @ 792~824, 896~960 40 @ 762~776, 20 @ 100~762, 10 @ 1000~1300	24.8 x 13 x 8.2
BPM866-03A1	865~868	3.0	15.0	40 @ 50~850 40 @ 885~2500	33.9 x 16.5 x 9.5
BPM866-03A2	865~868	3.0	15.0	40 @ 50~850 40 @ 885~2500	33.9 x 16.5 x 9.5
BPM871-68A1	837.5~905.5	0.55 at Fc	1.5:1	25 @ 700, 25 @ 1000	22.9 x 17.6 x 8.8
BPM881-25A1	869~894	2.5 at Fc	15.0	15 @ Fo±15	13 x 12 x 5
BPM881-25B1	869~894	2.0	1.5:1	38 @ Fo±80 43 @ Fo±100	13 x 12 x 4.7
BPM881-25C1	869~894	2.3	15.0	25 @ DC~849 35 @ 970~1200	13.5 x 8.4 x 6.2
BPM881-25D1	869~894	2.0	14.0	25 @ DC~849 35 @ 1015	13.5 x 12.7 x 6
BPM881-25E1	869~894	4.0	1.5:1	45 @ 780, 40 @ 849	32 x 17 x 4.7

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BPM881-25F1	869~894	3.5	15	60 @ 824~849, 30 @ <800 40 @ 925~1300, 8 @ 1300 ~1500, 2 @ 1500~2500	70 x 20 x 16.3
BPM881-25G1	869~890	3.0	15	60 @ 824~849	44.0x20.5x9.5
BNM886-02A1	885~887	3.0	2.0:1	7 @ 862, 17@ 910	60 x 22 x 10
BNM886-02B1	885~887	4.0	2.0:1	20 @ 862	7.6 x 9.05 x 3.7
BPM888-25A1	876~901	3.0	12.0	35 @ 705~735, 35 @ 540 ~565, 7.0 @ 921~946	8.7 x 9.2 x 3.9
BPM892-25A1	880~905	2.0	14.0	35 @ DC~840, 30 @ 925~1450	13.5 x 12.4 x 6
BNM897-35A1	880~915	4.0	1.7:1	20 @ 860, 935, 1500, 13 @ 925, 30 @ 1330	13.5 x 9.8 x 3.8
BPM897-35A1	880~915	5.0 @ Fc	15.0	30 @ 872.5 25 @ 922.5	42 x 17 x 9.5
BPM897-35B1	880~915	3.0	12.0	35 @ 710~750, 545~585 7.0 @ 925~960	8.7 x 9.1 x 3.9
BPM897-35C1	880~915	3.0	15.0	35 @ 925~960 25 @ <850, 960~1300	32.4 x 12.5 x 8.2
BNM898-06A1	895.5~901.5	3.0	2.0:1	30 @ 935	11.5 x 8.6 x 3.8
BHPM902-25A1	890~915	1.5	18	40@935~960	45x23x16.3
BNM902-25A1	889.5~914.5	2.6	2.3:1	27 @ 825, 9 @ 870 6.5 @ 935, 17 @ 980	5.6 x 8.5 x 2.8
BNM902-25A1	889.5~914.5	2.5	2.0:1	30 @ 825	8.16 x 8.75 x 2.8
BPM902-25A1	889.5~914.5	3.0	10	15 @ 870, 12 @ 935 45 @ 825, 28 @ 980	8.7 x 9.2 x 3.9
BPM902-25B1	890~915	2.0	14.0	35 @ DC~850 30 @ 935~1450	13.5 x 12.4 x 6.0
BPM902-25C1	890~915	3.3	15.0	8 @ 880, 25 @ 935~960	13 x 13.9 x 4.7
BPM902-25D1	890~915	4.0	1.5:1	40 @ 845, 935	32 x 17 x 4.7
BNM903-02A1	902~904	4.0	2.0:1	20 @ 878, 30 @ 928	7.6 x 8.9 x 3.6
BCM905-130A1	840~970	1.5	1.5:1	45 @ 777, 1068, 60 @DC~ 650, 950, 60 @ 1212~3000	32 x 17 x 7.5
BNM915-26A1	902~928	2.5	2.0:1	27 @ 837.5 17 @ 992.5	7.3 x 5.75 x 2.9
BNM915-26B1	902~928	2.5	2.0:1	23 @ 837.5 26 @ 992.5	7.3 x 5.75 x 2.85

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM915-26C1	902~928	2.5	2.0:1	35 @ 858 15 @ 893	17.5 x 8.5 x 5.69
BPM942-35A1	925~960	3.0	15.0	20 @ 880~915, 15 @ 880 20 @ 900~1300	32.4 x 12 x 8.2
BHPM947-25A1	935~960	1.5	18.0	40 @ 890~915	45x23x16.3
BPM947-25A1	935~960	2.0	14.0	30 @ DC~915 35 @ 1000~1350	13.5 x 11.8 x 6
BPM947-25B1	935~960	3.3	15	12 @ 925, 25 @ 890~915	13 x 13.9 x 4.7
BPM947-25C1	935~960	4.0	1.5:1	45 @ 845, 40 @ 915	32 x 17 x 4.7
BNM960-04B1	958~962	3.0	1.5:1	20 @ 930, 990	4 x 8.2 x 2
BNM978-05A1	975.5~980.5	2.8	1.5:1	30 @ 928, 1028	11 x 9.2 x 4.5
BPM1006-70A1	971~1041	2.5	15.0@Fc ±24	22.5 @ 1065.5~1165.5 12 @ 874~946.5, 53 @ 1198~1318, 50 @ 694~814	38.1 x 14 x 8
BNM1030-30A1	1015~1045	3.2@Fc	1.7:1	25 @ DC~900 20 @ 1090~1300	4 x 8.4 x 2
BPM1030-38A1	1011~1049	1.6@Fc	16	50 @ 990 50 @ 1070	67 x 15 x 12.3
BPM1090-08A1	1086~1094	7.0 at Fc	13	35 @ Fc±12 45 @ Fc±25	36 x 17 x 8.8
BNM1150-24A1	1138~1162	3.0	1.5:1	4.5 @ Fc±20 60 @ Fc-50, 55 @ Fc+50	22.9 x 13 x 6.1
BNM1150-24B1	1138~1162	3.0	1.5:1	4.5 @ Fc±20 60 @ Fc-50, 50 @ Fc+50	23.2 x 11 x 6.2
BNM1150-25A1	1137.5~1162.5	3.0	1.5:1	20 dBc @ 1080 60 @ Fc-50, 50 @ Fc+50	5.65 x 6.7 x 3.05
BNM1176-90A1	1131~1221	1.5	13	40 @ DC~650, 40 @ 1000, 1400, 40 @ 1700	10 x 9.5 x 4
BPM1200-40A1	1180~1220	2.0	14.0	60 @ 1270	26.5x13.5x9.5
BNM1202-106A1	1149~1255	1.5	14	40 @ DC~700, 1000, 1420, 38 @ 1750	10 x 9.2 x 4
BNM1210-126A1	1149~1273	1.5	12	40 @ DC~1010, 1450, 35 @ 1750	10 x 5.3 x 4
BNM1210-126A2	1149~1273	1.5	12	40 @ DC~1010, 1450, 35 @ 1750	10 x 5.3 x 3.7
DBPM1227-1575-20A1	1217~1237 1565~1585	3.0	1.5:1	50 @ 1000, 1405' 1800	25.0x16.0x5.0
BNM1227-20A1	1217.7~1237.7	1.5	2.0:1	30 @ 1127.72, 16 @ 1163.72, 12 @ 1277.72, 23 @ 1327.72	12 x 6.3 x 6

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM1227-20B1	1217.7~1237.7	2.0	2.0:1	30 @ 1127.72, 1327.72 20 @ 1163.72, 1277.72	17.3 x 6.3 x 6
BNM1227-90A1	1182~1272	1.5	13.0	40 @ DC~700, 1050 40 @ 1450, 1750	11 x 9.2 x 4
BNM1228-20A1	1217.6~1237.6	1.5	16	19 @ 1087.6 31 @ 1367.6	7.9 x 10.9 x 4.5
BNM1228-20B1	1217.6~1237.6	1.5	10	35 @ 1087.6, 30 @ 1367.6 7 @ 1192.6, 1262.6,	7.9 x 10.9 x 4.5
BNM1228-20B2	1217.6~1237.6	1.5	10	35 @ 1087.6, 30 @ 1367.6 7 @ 1192.6, 1262.6,	7.9 x 10.9 x 4.5
BPM1285-70A1	1250~1320	1.0	15	20 @ DC ~ 1188 20 @ 1375 ~ 2220	14.0x13.0x5.5
BPM1343-30A1	1328~1358	3.0	16	50 @ 1270, 1410 60 @ 2700	34.5 x 16.5 x 7.5
BPM1343-30B1	1328~1358	2.5	16	45 @ 1287, 1400	26 x 13 x 7.5
BPM1355-70A1	1320~1390	1.0	15	20 @ DC ~ 1251 20 @ 1542 ~ 2290	14.0x13.0x5.5
BPM1435-140A1	1365~1505	1.5	1.5:1	30 @ Fo±200	13.2 x 8.2 x 6.2
BPM1440-40A1	1420~1460	2.5	1.5:1	20 @ 1350~1390 20 @ 1485~1525	13.5 x 8.1 x 6.2
BNM1470-24A1	1458~1482	3.1	1.5:1	12 @ 1450, 1490 60 @ 1420, 1520	22.9 x 10.5 x 6.1
BNM1470-24B1	1458~1482	3.5	1.5:1	4.5 @ 1450, 1490 60 @ 1420, 1520	23.2 x 9 x 6.2
BPM1485-100A1	1435~1535	1.5	15.0	40 @ 1585	26.5x13.5x9.5
BPM1496-255A1	1369~1624	2.5	16	20 @ 1344, 1649 40 @ 1319~1674	45 x 13 x 9.2
BPM1496-255B1	1369~1624	3.0	16	10 @ 1344, 1649 30 @ 1319~1674	58 x 16 x 13.5
BPM1500-120A1	1440~1560	1.5 @ Fc	15	40 @ 1000~1420 40 @ 1580~1660	65 x 15 x 11.5
BPM1505-40A1	1485~1525	2.5	1.5:1	20 @ 1420~1460 20 @ 1555~1595	13.5 x 7.8 x 6.2
BPM1517-114A1	1460~1574	2.0	15	40 @ 1350, 22 @ 1425 22 @ 1610, 40 @ 1675	32.4 x 7.5 x 8
BNM1539-42A1	1518~1560	3.3 @ Fc	14.0	50 @ DC~1400, 37@ 1401 ~1467, 37 @ 1617~1817, 13 @ 1502~1576	28.1 x 8.4 x 6.2
BPM1539-42A1	1518~1560	3.3 @ Fc	14.0	50 @ DC~1400, 37@ 1401 ~1467, 37 @ 1617~10000 20 @ 10000~18000	31.75 x 12.7 x 8.13
BPM1539-42B1	1518~1560	3.0 @ Fc	15.0	35 @ DC~1576.5, 25 @ 1527, 20 @ 1623 40 @ 1750~20000	30 x 12 x 8.8
BNM1542-34A1	1525~1559	3.5	15.0	10 @ 1610, 30 @ 1626.5~1660	11.5 x 8 x 3.8

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM1542-100A1	1492~1592	1.5	14.0	40 @ DC~970, 1370, 1770, 38 @ 2170	10 x 7 x 4
BPM1555-20A1	1545~1565	2.5	15.0	40 @ 1510, 40 @ 1610	40.5 x 7.5 x 8
BNM1556-95A1	1508~1603	1.5	14.0	40 @ DC~1000,1370, 1790, 38 @ 2180	10 x 7 x 4
BNM1563-127A1	1500~1627	1.5	14.0	40 @DC~1000,1370, 1790 38 @ 2180	10.0x7.0x4.0
BNM1568-120A1	1508~1628	1.5	14.0	40 @ DC~1000,1380, 1800, 38 @ 2200	10 x 6.8 x 4
BNM1568-120A2	1508~1628	1.5	14.0	40 @ DC~1000,1380, 1800, 38 @ 2200	10 x 6.5 x 3.7
BNM1575-02A1	1574.4~1576.4	2.0	2.0:1	18 @ 1525, 1625 10 @ 1545, 1605	7 x 4.7 x 3
BNM1575-06A1	1572.42~1578.42	2.6	2.0:1	16 @ 1435.42 14 @ 1715.42	6.85 x 4.65 x 2.8
BNM1575-10A1	1570.42~1580.42	3.0	2.0:1	20 @ 1525.42, 15 @ 1625.42, 25 @ 1675.42	5.8 x 5.25 x 2.8
BNM1575-10A2	1570.42~1580.42	3.0	2.0:1	20 @ 1525.42, 15 @ 1625.42, 25 @ 1675.42	5.8 x 5.25 x 2.8
BNM1575-11A1	1570~1581	1.5	16	7@ 1501, 20 @ 1625	7.88 x 9.15 x 4.52
BNM1575-20A1	1565.42~1585.42	1.5	10.0	10 @ 1500.4, 6 @ 1525, 17 @1625, 32 @1650	7.9 x 9.27 x 4.5
BNM1575-20B1	1565.42~1585.42	1.5	2.0:1	30 @ 1475.4, 16 @ 1525, 12 @ 1625, 23 @ 1650	12 x 7.7 x 6
BNM1575-20C1	1565.42~1585.42	2.0	2.0:1	30 @ 1475.4, 1675, 20 @ 1525, 1625	17.3 x 7.7 x 6
BNM1575-20D1	1565.42~1585.42	1.5	2.0:1	30 @ 1475.4, 1675, 20 @ 1525, 1625	17.3 x 7.7 x 6
BPM1575-20A1	1565.42~1585.42	1.0	15.0	35 @ 100~1415 & 1800	20 x 12 x 7
BNM1575-100A1	1525~1625	1.5	14.0	40 @ DC~1000,1400, 1800, 38 @ 2200	10 x 6.8 x 4
BNM1575-100B1	1525~1625	1.5	2.0:1	7 @ 1500.42 1800	7.62 x 8.89 x 4.3
BPM1587-55A1	1559.7~1614.6	1.5	15.0	20 @ 1544.8	45 x 17 x 16.5
BPM1587-56A1	1559~1615	2.7	16.0	50 @ 1544	70.0x22.0x16.5
BPM1601-70A1	1566~1636	2.5 @ Fc	15@Fc±24	12 @1660.5~1760, 22 @ 1442~1541.5, 50 @ 1793 ~1913, 55 @ 1289~1409	17.3 x 12.7 x 6.1
BNM1643-34A1	1626.5~1660.5	3.0	15	25 @ 1525~1559 24.5 @ 1751.5	11.5 x 8 x 3.8

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BPM1643-34A1	1626.5~1660.5	2.2	10	30.5 @ 1578.5, 24.5 @ 1751.5	11.75 x 7.32 x 4.5
BPM1643-34B1	1626.5~1660.5	3.0	1.7:1	50 @ 1558.5, 1728.5	18.5 x 10.2 x 7.2
BPM1643-34C1	1626.5~1660.5	1.0	1.7:1	35 @ 1558.5, 1728.5	22 x 7.2 x 8.2
BPM1650-49A1	1626~1675	3.0	15	35 @ DC~1576.5 25 @ Fc-48, 20 @ Fc+48, 40 @ 1750~2000 20 @ 5500~10000	31.75 x 12.7 x 8.1
BPM1650-49B1	1626~1675	4.0	15	30 @ DC~1576.5 15 @ Fc±48, 40 @ 1750~2000	14 x 12 x 4.5
BNM1660-30A1	1645~1675	3.0	15	20 @ 1500,1575, 1775, 1820	11.75 x 7.3 x 4.5
BPM1675-20A1	1665~1685	3.2 @ Fc	1.5:1	30 @ Fo±35	22.9 x 8.7 x 8.2
BPM1675-100A1	1625~1725	1.8	1.5:1	40 @ Fo±125	22.9 x 8.7 x 8.2
BNM1687-02A1	1686.5~1688.5	5.0	12.0	60 @ 1575, 1800	27.9 x 6.52 x 5
BPM1688-108A1	1634~1742	2.5	16.0	20 @ 1609, 1767 40 @ 1534, 1792	45 x 13 x 9.2
BPM1688-108A2	1634~1742	2.5	16.0	20 @ 1609, 1767 40 @ 1534, 1792	45 x 13 x 9.2
BPM1700-20A1	1690~1710	2.5	15	40dBc @ DC ~ 1600 40dBc @ 1800 ~ 2800	19.0x12.0x4.3
BPM1700-20A2	1690~1710	4.5	15	40dBc @ DC ~ 1600 40dBc @ 1800 ~ 4000 20dBc @ 4000 ~ 6000 15dBc @ 8000 ~ 12000	19.0x12.0x4.3
BPM1700-20A3	1690~1710	7.0@Fc	15@Fc	3dBc @ 1690, 1710 40dBc @ DC ~ 1600 40dBc @ 1800 ~ 4000 15dBc @ 4000 ~ 5000	19.0x12.0x4.3
BPM1732-45A1	1710~1755	2.7	12.0	35 @ 1615, 48 @ 1850	13 x 12 x 5
BPM1732-45B1	1710~1755	2.5	1.5:1	20 @ 800~1690, 20 @ 1755~1850, 35 @ 1850 ~1930, 50 @ 1930~2170	43 x 18 x 9.2
BNM1733-10A1	1728~1738	3.5	10	12 @ 1705, 15 @ 1758	11.4 x 7.3 x 3.8
BPM1735-26A1	1722~1748	2.3	15.0	15 @ 1783, 1687 45 @ 1878, 1592	13 x 12 x 4.7
BPM1737-55A1	1710~1765	2.0	14.0	22 @ <1665, 22 @ >1810	17.3 x 6.2 x 8.2
BPM1738-15A1	1730.6~1745.6	3.5	1.5:1	10 @ Fo±37.5	13 x 12 x 4.7
BNM1740-16A1	1732~1748	4.5	14	40 @ DC~ 1690, 1790~ 3800, 42 @ 1700, 1780 30 @ 3800~6000	26.4 x 13.7 x 4.8



Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM1740-24A1	1728~1752	3.5	2.0:1	45 @ DC~ 1680,1690~1790, 45 @ 1800, 3800 30 @ 3800~6000	33.8 x 13.7 x 6.9
BPM1741-08A1	1737.5~1745.5	3.5	1.5:1	10 @ Fo±34.0	13 x 12 x 4.7
BPM1745-70A1	1710~1780	2.0	15.0	65 @ 2110~2180	44.0x20.5x9.5
BPM1747-75A1	1710~1785	3.6	10.0	8 @ 1795	13 x 12 x 5
BPM1747-75B1	1710~1785	3.6 @ Fc	2.0:1	15 @ 1795 40 @ 1805~1880	42 x 17 x 8.8
BPM1747-85A1	1705~1790	1.5	1.5:1	6 @ 1805, 50 @ 960	13 x 12 x 4.7
BPM1754-23A1	1743.1~1766.1	3.0	1.5:1	22 @ Fo±47.5	13 x 12 x 4.7
BNM1755-10A1	1750~1760	3.3	10	50 @ 1685	11.38 x 6.58 x 3.7
BPM1757-04A1	1755.9~1759.9	3.5	1.5:1	10 @ Fo±32.0	13 x 12 x 4.7
BPM1757-55A1	1730~1785	2.0	14.0	22 @ <1685, 22 @ >1830	17.3 x 6.2 x 8.2
BPM1757-55B1	1730~1785	2.3	14.0	25 @ 1690, 1825 6 @ 1805	13.5 x 8.4 x 6.2
BPM1758-12A1	1752.5~1764.5	3.5	1.5:1	10 @ Fo±36.0	13 x 12 x 4.7
BPM1770-30A1	1755~1785	2.2	18.0	45 @ 1880, 35 @ 1660	13 x 12 x 5
BPM1772-30A1	1757.5~1787.5	1.5	15.0	20 @ 1867.5	13 x 12 x 4.6
BNM1795-170A1	1710~1880	1.0	15	30 @ 1580	11 x 6.6 x 4.3
BNM1795-170B1	1710~1880	1.5	15	30 @ 1580	11 x 6.6 x 4.3
BPM1800-20A1	1790~1810	2.5	15	40dBc @ DC ~ 1700 40dBc @ 1900 ~ 2800	19.0x12.0x4.3
BPM1800-20A2	1790~1810	4.5	15	40dBc @ DC ~ 1700 40dBc @ 1900 ~ 4000 20dBc @ 4000 ~ 6000 15dBc @ 8000 ~ 12000	19.0x12.0x4.3
BPM1800-20A3	1790~1810	7.0@Fc	15@Fc	3dBc @ 1790, 1810 40dBc @ DC ~ 1700 40dBc @ 1900 ~ 4000 15dBc @ 4000 ~ 5000	19.0x12.0x4.3
BPM1800-50A1	1775~1825	2.0	14.0	49 @ 1550, 2050	13.5x12.5x5.5
BPM1800-100A1	1750~1850	1.0	15.0	20 @ DC ~ 1665 20 @ 1925 ~ 2825	14.0x13.0x5.5
BPM1800-800A1	1400~2200	2.0@Fc	2.0:1	50 @ DC~400, 30@400 ~1100, 10@2500~3000	13.5x12.5x5.5

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BPM1815-70A1	1780~1850	1.5	15	45@1700, 40@1930	22.7x10.8x8.1
BPM1817-65A1	1785~1850	2.0	15	45@1705, 40@1930	38.1x12.7x9.0
BPM1830-26A1	1817~1843	2.3	15	15 @ 1782, 1878 45 @ 1687, 1973	13 x 12 x 4.7
BPM1832-55A1	1805~1860	2.0	14.0	22 @ <1760, 22 @ >1905	17.3 x 6.2 x 8.2
BPM1833-15A1	1825.6~1840.6	3.5	1.5:1	10 @ Fo±37.5	13 x 12 x 4.7
BPM1836-08A1	1832.5~1840.5	3.5	1.5:1	10 @ Fo±34.0	13 x 12 x 4.7
BNM1842-75A1	1805~1880	2.0	2.0:1	14 @ 1705, 4 @ 1920	13 x 12 x 5
BPM1842-75A1	1805~1880	3.6 @ Fc	10.0	8 @ 1795	13 x 12 x 5
BPM1842-75B1	1805~1880	3.6 @ Fc	2.0:1	15 @ 1795 40 @ 1710~1785	42 x 17 x 8.8
BPM1842-75C1	1805~1880	3.0	15.0	23 @ 1710~1785, 23 @ 1920~1980, 25 @ <1710 20 @ 1980~2500	32.4 x 8.2 x 8.2
BPM1849-23A1	1838.1~1861.1	3.0	1.5:1	22 @ Fo±47.5	13 x 12 x 4.7
BPM1850-57A1	1821.5~1878.5	3.0	12	30 @ DC~1808 30 @ 1892~2500	42 x 13 x 9.0
BPM1852-04A1	1850.9~1854.9	3.5	1.5:1	10 @ Fo±32.0	13 x 12 x 4.7
BPM1852-55A1	1825~1880	2.0	14.0	22 @ <1780, 22 @ >1925	17.3 x 6.2 x 8.2
BPM1852-55B1	1825~1880	2.3	14.0	25 @ 1785& 1920 6 @ 1805	13.5 x 8 x 6.2
BPM1853-12A1	1847.5~1859.5	3.5	1.5:1	10 @ Fo±36.0	13 x 12 x 4.7
BNM1855-10A1	1850~1860	3.5	2.0:1	13 @ 1830, 18 @ 1880	11.25 x 6.2 x 3.65
BPM1865-30A1	1850~1880	2.2	18.0	45 @ 1755, 35 @ 1975	13 x 12 x 5
BPM1867-30A1	1852.5~1882.5	1.5	15.0	20 @ 1772.5	13 x 12 x 4.6
BPM1867-35A1	1850~1885	3.0	12.0	30 @ 1930~1965 15 @ 1907, 35 @ 1720	13 x 12 x 5
BPM1880-32A1	1864~1896	2.2	15.0	20 @ 1944~1976	13 x 12 x 4.6
BNM1880-60A1	1850~1910	2.4	2.0:1	10 @ 1780 5 @ 1980	5.8 x 5.9 x 2.9
BNM1880-60B1	1850~1910	2.4	2.0:1	20 @ 1780 20 @ 1980	7.52 x 3.95 x 2.9
BNM1880-60C1	1850~1910	2.2	2.0:1	15 @ 1780 15 @ 1980	7.6 x 3.95 x 2.8

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM1880-60D1	1850~1910	2.4	2.0:1	15 @ 1780 15 @ 1980	7.6 x 3.95 x 2.9
BPM1880-60A1	1850~1910	5.0	2.0:1	15 @ 1780 30 @ 1930	23 x 14.5 x 7.5
BPM1880-60B1	1850~1910	3.6	13.0	8 @ 1920	13 x 12 x 5
BPM1880-60C1	1850~1910	2.5	1.5:1	30 @ 800~1710, 35 @ 1710~1755, 50 @ 1930~ 1995, 50 @ 2100~2170 5 @ 2170~3500	67 x 18 x 10.3
BPM1880-60D1	1850~1910	2.0	14.0	20 @ DC~1810 8 @ > 1930	17.3 x 6.2 x 7.6
BPM1880-60E1	1850~1910	3.0	15.0	40 @ 800~1755 50 @ 1930~2170	43.5x13.0x9.0
BPM1882-65A1	1850~1915	3.0	1.5:1	25 @ 1930~1995, 25 @ 1710~1770, 25 @ 2110~ 2170, 25 @ 100~1000	32.5 x 8.1 x 8.2
BPM1882-65B1	1850~1915	2.0	14.0	25 @ 1810 5 @ 1930	13.5 x 7 x 6
BNM1890-20A1	1880~1900	1.8	2.0:1	30 @ 1660~1680, 15 @ 3760~3800, 10 @ 5640~5700	7.45 x 4.1 x 3.3
BNM1890-20B1	1880~1900	1.3	2.0:1	40 @ 1650, 8 @ 1780, 6 @ 2000	3.9 x 4.1 x 1.9
BPM1897-25A1	1885~1910	3.0	12.0	30 @ 1965~1990 35 @ 1755, 15 @ 1937	13 x 12 x 5
BPM1900-20A1	1890~1910	2.5	15	40dBc @ DC ~ 1800 40dBc @ 2000 ~ 2900	19.0x12.0x4.3
BPM1900-20A2	1890~1910	4.5	15	40dBc @ DC ~ 1800 40dBc @ 2000 ~ 4000 20dBc @ 4000 ~ 6000 15dBc @ 8000 ~ 12000	19.0x12.0x4.3
BPM1900-20A3	1890~1910	7.0@Fc	15@Fc	3dBc @ 1890, 1910 40dBc @ DC ~ 1800 40dBc @ 2000 ~ 4000 15dBc @ 4000 ~ 5000	19.0x12.0x4.3
BNM1912-05A1	1910~1915	3.0	2.0:1	30 @ 1990	8.4 x 5.1 x 3
BPM1947-35A1	1930~1965	3.0	12.0	30 @ 1850~1885 35 @ 2095, 15 @ 1908	13 x 12 x 5
BNM1950-60A1	1920~1980	3.0	2.0:1	25 @ 2140	5.7 x 4.7 x 2
BPM1950-60A1	1920~1980	2.0	14.0	38 @DC~1930, 35 @2070 ~3000, 30 @ 3000~3500	17.3 x 6.2 x 7.3
BPM1950-60B1	1920~1980	2.0	14.0	30 @ 1840, 2110 8 @ 2045	13.5 x 7.7 x 6.2
BPM1960-20A1	1950~1970	2.5	17.0	45@1883.2	13.5x12.5x5.5
BPM1960-32A1	1944~1976	2.2	15.0	20 @ 1864~1896	13 x 12 x 4.6
BPM1960-34A1	1943~1977	4.5	18.0	10@1938,1982	42.5x17.5x9.5

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM1960-60A1	1930~1990	3.0	2.0:1	17 @ DC~1830, 3@1830~1910, 2@2010~2070, 9@2070~2400, 20@2400~2500, 15@2500~4000	3.7 x 4 x 1.6
BNM1960-60B1	1930~1990	1.9	2.0:1	20 @ 1910	4.3 x 4.2 x 1.9
BNM1960-60C1	1930~1990	2.4	2.0:1	48 @ 1560, 40 @ 2360, 18 @ 1860, 2060	7.52 x 3.8 x 2.9
BNM1960-60D1	1930~1990	3.3	2.0:1	20 @ 1910	7.7 x 6.45 x 2.6
BPM1960-60A1	1930~1990	2.5	15.0	20 @ Fc±100	13 x 12 x 5
BPM1960-60B1	1930~1990	2.0	14.0	8 @ DC~1910 20 @ > 2030	17.3 x 6.2 x 7.6
BPM1960-60C1	1930~1990	3.6	13.0	8 @ 1820	13 x 12 x 5
BPM1960-60D1	1930~1990	3.0	1.5:1	30 @800~1710, 55 @1710~1755, 55 @ 1850~1910 40 @ 2100~2170 5 @ 2170~3500	67 x 18 x 11.3
BPM1960-60E1	1930~1990	4.0	15.0	40 @ 800~1785,2100~2170 50 @ 1850~1910	43.5x13.0x9.0
BPM1962-65A1	1930~1995	2.0	14.0	25 @ 2030 5 @ 1915, 2 @ 1922.5	13.5 x 7 x 6
BPM1962-65B1	1930~1995	3.0	1.5:1	25 @ 1850~1915, 25 @ 1710~1850, 25 @ 2110~2170, 25 @ 100~1000	32.5 x 8.1 x 8.2
BPM1962-65C1	1930~1995	3.0	1.5:1	18 @ 1850~1915, 25 @ 1710~1850, 25 @ 2110~2170, 25 @ 100~1000	32.5 x 7.3 x 8.2
BPM1962-65D1	1930~1995	5.5	16	25 @ 1922.5 60 @ 1850~1915	44.0x13.5x9.5
BPM1962-65E1	1930~1995	3.5	18	50 @ 1850~1915	66.0x16.0x10.5
BPM1977-25A1	1965~1990	3.0	12.0	30 @ 1885~1910 35 @ 2120, 15 @ 1938	13 x 12 x 5
BPM2017-15A1	2010~2025	2.8	1.3:1	47dBc @ DC~1980,2055~2200 40dBc @ 2200 ~ 3000	33.4x11.5x9.0
BPM2020-60A1	1990~2050	2.7	14.0	25 @ 2110~2170	10.8 x 7.3 x 3.7
BNM2140-60A1	2110~2170	3.0	2.0:1	40 @ 1950	5.7 x 4.7 x 2
BNM2140-60B1	2110~2170	2.0	2.0:1	35 @ 2400	8.47 x 5.3 x 3.04
BPM2140-60A1	2110~2170	2.0	14.0	38 @ DC~2020 35 @ 2250~3700	17.3 x 6.2 x 6.58
BPM2140-60B1	2110~2170	2.0	14.0	30 @ 1980, 2250 8 @ 2045	13.5 x 7 x 6.2
BPM2145-70A1	2110~2180	2.0	15.0	50 @ 1710~1780	44.0x20.5x9.5

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BPM2200-01A1	2199.5~2200.5	2.0	15.0	60 @ 2100, 60 @ 2300	42 x 12 x 9
BPM2200-16A1	2192~2208	5.0	16.0	65 @ 2150, 65 @ 2250	48.1 x 10.9 x 8.9
BNM2200-30A1	2190~2210	2.6	10.0	36@824~1910, 30@1980~ 2020, 15@2025~2170, 15@ 2270~2285, 20@ 2290~3200	13.5x12.5x4.5
BPM2200-1000A1	1700~2700	2.0@Fc	2.0:1	50@DC~500, 30@500~ 1400, 10@3100~4600	13.0x12.5x5.5
BNM2248-96A1	2200~2296	3.0	12.0	43 @ 2354~2380	14 x 6.1 x 4.5
BPM2250-100A1	2200~2300	1.5	15.0	20@2170, 2400	38.1x12.7x9.0
BPM2250-100B1	2200~2300	1.0	15.0	20@2170, 2400	31.0x15.0x11.5
BPM2250-100C1	2200~2300	3.0	15.0	20@2170, 2400	24.0x10.7x7.5
BPM2250-120A1	2190~2310	1.5	15.0	60@2100	26.5x13.5x9.5
BNM2310-10A1	2305~2315	3.0	1.5:1	50 @ 1830, 45 @ 2070, 20 @ 2260, 2360	8.25 x 7 x 3
BNM2310-10A2	2305~2315	3.0	1.5:1	50 @ 1830, 45 @ 2070, 20 @ 2260, 2360	8.4 x 5.2 x 3
BNM2310-10B1	2305~2315	3.5	12	43 @ 2345~2360	14.8 x 6.8 x 5.4
BNM2317-30A1	2302~2332	3.5	12	43 @ 2376~2400	14.8 x 6.8 x 5.4
BNM2323-30A1	2308~2338	3.0	1.5:1	35 @ 1500, 2066~2096, 3000, 40@1824~1858, 30 @ 2188~2218, 15 @ 2402~2432	8.25 x 7 x 3
BNM2323-30A2	2308~2338	3.0	1.5:1	35 @ 1500, 2066~2096, 3000, 40 @ 1824~1858, 30 @ 2188~2218, 15 @ 2402~2432	8.4 x 5.2 x 3
BNM2332-25A1	2320~2345	3.0	2.0:1	35 @ 2106, 2571	5.8 x 5.2 x 3
BNM2332-25B1	2320~2345	3.0	2.0:1	35 @ 450, 824~894, 1433 1850~1990, 2106, 2571	5.8 x 5.2 x 3
BNM2332-25B2	2320~2345	3.0	2.0:1	35 @ 450, 824~894, 1433 1850~1990, 2106, 2571	5.55 x 5.15 x 3
BNM2332-25C1	2320~2345	2.0	2.0:1	35 @ 450, 824~894, 1433 1850~1990, 2106, 27 @ 2571	5.55 x 5.15 x 3
BNM2332-25D1	2320~2345	2.0	2.0:1	35 @ 450, 824~894, 1433 1850~1990, 2106, 30 @ 2571	5.55 x 5.15 x 3
BNM2338-13A1	2332.5~2345	3.0	2.0:1	25 @ 2109, 2568	5.5 x 5.2 x 2.75
BNM2338-30A1	2323~2353	3.0	1.5:1	35 @ 1500, 2081~2111, 3000, 40 @ 1839~1873, 30 @ 2203~2233, 15 @ 2417~2447	8.4 x 5.1 x 3

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM2355-10A1	2350~2360	3.0	1.5:1	50 @ 1875, 45 @ 2115, 20 @ 2305 2405	8.25 x 7 x 3
BNM2355-10A2	2350~2360	3.0	1.5:1	50 @ 1875, 45 @ 2115, 20 @ 2305 2405	8.4 x 5.1 x 3
BNM2355-10B1	2350~2360	3.5	12	43 @ 2305~2315	14.8 x 6.8 x 5.4
BNM2355-30A1	2340~2370	3.0	1.5:1	35 @DC~1500, 3000, 2098~2128, 40 @ 1856~1886, 30 @ 2219~2249, 15 @ 2434~2464	8.4 x 5.1 x 3
BNM2358-24A1	2346~2370	3.0	1.5:1	35 @ 2500, 2104~2128, 4000, 40 @ 1862~1886, 30 @ 2225~2249, 20 @ 2440~2464	8.4 x 5.1 x 3
BNM2358-24B1	2346~2370	3.0	1.5:1	30 @ 2500, 2225~2249, 40 @ 1862~1886, 35 @ 2104~, 2128, 18 @ 2440~2464, 4000	8.4 x 5.1 x 3
BNM2358-30A1	2343~2373	3.0	1.5:1	35 @ 1500, 2101~2131, 3000, 40 @ 1859~1893, 30 @ 2223~2253, 15 @ 2437~2467	8.4 x 5.1 x 3
BNM2367-26A1	2354~2380	3.0	12	43 @ 2200~2296	14 x 5 x 4.5
BPM2375-60A1	2345~2405	1.7	1.5:1	30 @ 2195, 2555	13.2 x 6.3 x 6.2
BPM2388-24A1	2376~2400	3.5	12	43 @ 2302~2332	14.8 x 6.8 x 5.4
BNM2417-30A1	2402~2432	3.0	1.5:1	35@1500, 3000, 40 @ 1918~1952, 30 @ 2162~2192, 28 @ 2282~2312, 15 @ 2312~2338	8.25 x 7.0 x 3
BNM2417-30A2	2402~2432	3.0	1.5:1	35 @ 1500, 3000, 40 @ 1918~1952, 30 @ 2162~2192, 28 @ 2282~2312, 15 @ 2312~2338	8.4 x 5.1 x 3
BNM2432-30A1	2417~2447	3.0	1.5:1	35 @ 1500, 2177~2207, 3000, 40 @ 1933~1967, 30 @ 2297~2327, 15 @ 2327~2353	8.4 x 5.1 x 3
BNM2437-50A1	2412~2462	2.0	12	7 @ 2390, 2485	10.64 x 8.4 x 3.85
BNM2437-50B1	2412~2462	2.5	12	4 @ 2416, 2473, 45 @DC~2300, 30 @ 2570~3360, 20 @ 3300~3500, 2390, 2485, 5 @ 3500~4000	28.6 x 9.2 x 8.0
BPM2437-50A1	2412~2462	3.0	1.7:1	20 @ 2390, 2483, 30 @ DC~2300, 2570~3500	25.3 x 9.3 x 8.2
BPM2437-50B1	2412~2462	3.2	1.7:1	20 @ 2300~2390, 2483~2570, 30 @ 2300, 2570	26.5 x 5.5 x 8
BNM2441-83A1	2400~2483	1.2	2.0:1	16 @ 2191, 12 @ 2691	3.7 x 4.2 x 1.9
BNM2441-83B1	2400~2483	2.0	15	18@2100~2300, 2600~ 2800, 25@1200~1250, 3600~3750	8.5x6.5x3.3

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM2442-84A1	2400~2484	2.0	2.0:1	19 @ 2192, 14 @ 2692	3.7 x 4.3 x 2
BNM2442-84B1	2400~2484	3.0	2.0:1	45 @ 1942, 40 @ 2192, 2942, 25 @ 2692	5.7 x 4.35 x 2.1
BNM2447-30A1	2432~2462	3.0	1.5:1	35@1500, 2192~2222,40 @1948~1982, 30 @ 2312 ~2342, 15 @ 2342~2368	8.4 x 5 x 3
BNM2449-30A1	2434~2464	3.0	1.5:1	35 @DC~1500,2194~2224, 3000, 40 @ 1954~1984, 30 @ 2314~2344, 15 @ 2344~2370	8.4 x 5.1 x 3
BNM2450-100A1	2400~2500	2.0	2.0:1	23 @ 2170, 12 @ 2730	5.8 x 4.8 x 1.7
BNM2450-100B1	2400~2500	2.0	2.0:1	25 @ 2170, 14 @ 2730	5.85 x 4.75 x 2.05
BNM2452-24A1	2440~2464	3.0	1.5:1	35 @2500, 2198~2222, 4000, 40 @ 1956~1980, 30 @ 2319~2343, 20 @ 2346 ~2370, 17 @ 2370~2394	8.4 x 5.1 x 3.0
BNM2452-24B1	2440~2464	3.0	1.5:1	8 @2500, 18 @4000, 35 @ 2198~2222, 40 @ 1956~1980, 30 @ 2319~2343, 20 @ 2346~2370,	8.4 x 5.1 x 3
BPM2475-10A1	2470~2480	2.5	18.0	40 @ 2425.5, 2525.5	22 x 6.7 x 4.5
BNM2500-400A1	2300~2700	1.5	12.0	25@2110 ~2170, 35@1800 ~1990, 15 @ 4600 ~4500	13.4 x 8.8 x 4.1
BPM2535-70A1	2500~2570	2.0	15.0	40 @ 2620 ~2690	35 x 15 x 12
BPM2535-70B1	2500~2570	1.5	15.0	30 @ 2620 ~2690	30 x 15 x 12
BPM2535-70C1	2500~2570	1.0	15.0	20 @ 2620 ~2690	25 x 15 x 12
BPM2535-70D1	2500~2570	0.5	15.0	5 @ 2620 ~2690	20 x 15 x 12
BPM2535-70E1	2500~2570	4.0	15.0	70 @ 2620 ~2690	67 x 15 x 12
BPM2655-70A1	2620~2690	2.0	15.0	40 @ 2500~2570	35 x 15 x 12
BPM2655-70B1	2620~2690	1.5	15.0	30 @ 2500~2570	30 x 15 x 12
BPM2655-70C1	2620~2690	1.0	15.0	20 @ 2500~2570	25 x 15 x 12
BPM2655-70D1	2620~2690	0.5	15.0	5 @ 2500~2570	20 x 15 x 12
BPM2655-70E1	2620~2690	4.0	15.0	70 @ 2500~2570	67 x 15 x 12

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BPM2700-30A1	2685~2715	3.0	18.0	50@2600, 2800	12.7x12.5x5.7
BPM2700-30B1	2685~2715	3.0	15.0	40dBc@DC ~ 2600 32dBc@2800 ~ 3500	19.0x12.0x4.3
BPM2700-30B2	2685~2715	5.0	15.0	40dBc@DC ~ 2600 40dBc@2800 ~ 4000 20dBc@4000 ~ 6000 15dBc@8000 ~ 12000	19.0x12.0x4.3
BPM2700-30B3	2685~2715	6.5@Fc	15.0	3dBc@2685, 2715 40dBc@DC ~ 2600 40dBc@2800 ~ 4000 15dBc@4000 ~ 5000	19.0x12.0x4.3
BPM2745-110A1	2690~2800	1.5 @ Fc	1.5:1	30 @ Fo+200 20 @ Fo-200	10 x 10 x 4.3
BPM2750-30A1	2735~2765	2.5 @ Fc	16	45 @ 2690, 2810	26 x 13 x 7.5
BNM2800-200A1	2700~2900	2.2	15.0	13 @ 2670 & 2930 30 @ 2630 & 2970	32.5x9.5x8.44
BPM2800-200A1	2700~2900	2.0	15.0	13 @ 2670 & 2930 30 @ 2630 & 2970	38.1x14.0x9.0
BPM2800-800A1	2400~3200	2.0@Fc	2.0:1	50@DC~700, 30@700~1400 18@3800~4800	13.0x12.5x5.5
BPM2825-230A1	2710~2940	3.5@Fc	15	12@Fc±135, 20@Fc±149, 30@Fc±165, 35@Fc±185, 30@Fc±365~1115	29.5x12.0x7.5
BPM2832-30A1	2817~2847	2.5 @ Fc	16	45 @ 2772, 2892	26 x 13 x 7.5
BPM2900-400A1	2700~3100	2.0	15.0	60 @ 2500 & 3300	40.5 x 7.9 x 8
BPM2925-230A1	2810~3040	3.5@Fc	15	12@Fc±135, 20@Fc±149, 30@Fc±165, 35@Fc±185, 30@Fc±365~1115	29.5x12.0x7.5
BPM3075-230A1	2960~3190	3.5@Fc	15	12@Fc±135, 20@Fc±149, 30@Fc±165, 35@Fc±185, 30@Fc±365~1115	29.5x12.0x7.5
BNM3300-15A1	3292.5~3307.5	3.0	2.0:1	35 @ 3140, 3220, 3480	18.4 x 8 x 5.4
BNM3300-30A1	3285~3315	3.0	2.0:1	35 @ 3140, 3220, 3480	18.4 x 7.35 x 5.4
BNM3300-30A2	3285~3315	3.0	2.0:1	35 @ 3140, 3220, 3480	18.4 x 8.4 x 5.4
BNM3300-30B1	3285~3315	4.0	2.0:1	35 @ 3220, 3380	18.4 x 8.4 x 5.4
BNM3318-12B1	3312~3324	3.0	1.5:1	35@DC~2500,3070~ 3082, 4000, 40@2828~2840, 30 @ 3191~3203, 15 @ 3242 ~3454, 12 @ 3388~3400	8.3 x 7.7 x 3.0



Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM3318-12A1	3312~3324	3.0	14	35@DC~2500,3070~ 3082, 4000, 40 @ 2828~2840, 30 @ 3191~3203, 15@3242~3454, 12 @ 3388~3400	8.4 x 5.6 x 2.8
BNM3318-12C1	3312~3324	3.0	1.5:1	35 @ DC~2500,30703082, 4000, 40@2828~2840, 30 @3191~3203, 15@ 3242~3454, 30 @ 3388~3400	8.3 x 7.7 x 3
BPM3325-230A1	3210~3440	3.5@Fc	15	12@Fc±135, 20@Fc±149, 30@Fc±165, 35@Fc±185, 30@Fc±365~1115	29.5x12.0x7.5
BPX3360-08A1	3356~3364	3.0@Fc	1.5:1	40 @ 3100, 3620	21.3x15.0x7.5
BNM3380-30A1	3365~3395	3.0	2.0:1	35 @ 3220, 3300, 3560	18.4 x 7.9 x 5.4
BNM3380-30A2	3365~3395	3.0	2.0:1	35 @ 3220, 3300, 3560	18.4 x 8.4 x 5.4
BNM3380-30B1	3365~3395	4.0	2.0:1	35 @ 3300, 3460	18.4 x 7.9 x 5.4
BNM3394-12A1	3388~3400	3.0	14	35 @ DC~2500, 3146~3158, 4000, 40 @ 2904~2916, 30 @ 3267~3279, 20 @ 3312~3324	8.4 x 5.6 x 2.8
BNM3394-12A2	3388~3400	3.0	14	35 @ DC~2500, 3146~3158, 4000, 40 @ 2904~2916, 30 @ 3267~3279, 20 @ 3312~3324	8.4 x 7.7 x 3
BNM3400-200A1	3300~3500	4.0	2.0:1	50 @ 2745, 35 @ 3120 30 @ 3770	15 x 6.2 x 3.85
BNM3405-190A1	3310~3500	4.0	2.0:1	50 @ 2750, 35 @ 3125 30 @ 3775	15 x 6.2 x 3.85
BNM3415-30A1	3400~3430	4.0	2.0:1	35 @ 3500~3530	10 x 4.8 x 4
BNM3415-30B1	3400~3430	3.0	1.5:1	35 @ DC~2452.5, >3952, 3161~3188,40 @ 2917~2948, 30 @ 3280~3307, 15 @ 3501~3528	8.3 x 7.5 x 3
BNM3415-30C1	3400~3430	3.0	1.5:1	35 @DC~2452.5, >3952, 40 @ 2917~2948,30 @ 3161~3188,10 @ 3470~3500, 15 @ 3280~3307, 25 @ 3501~3528	8.3 x 7.5 x 3
BNM3415-30D1	3400~3430	3.0	1.5:1	35 @DC~2452.5, >3952, 3161~3188,40 @ 2917~2948, 25 @ 3280~3307, 15 @ 3470~3500	8.6 x 7.6 x 3
BNM3420-42A1	3399.5~3441.5	2.5	1.5:1	35 @ DC~2500, >4000, 3000~3041,40 @ 2600~2640, 15 @ 3499~3541	8.3 x 5 x 3
BNM3420-42B1	3399.5~3441.5	2.5	1.5:1	35 @ DC~2500, >4000, 3160~3201,40 @ 2916~2961, 20 @ 3279~3320 10@3499~3541	8.3 x 4.5 x 3
BNM3420-42C1	3399.5~3441.5	2.5	1.5:1	35 @ DC~2500, 3160~3201 >4000, 40 @ 2916~2961, 30 @ 3279~3320, 15 @ 3499~3541	15 x 4.5 x 3.9
BNM3424-28A1	3410~3438	3.0	1.5:1	40 @ 3524 35 @ 3224	18.5 x 8.25 x 5.7

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM3425-50A1	3400~3450	3.5	2.0:1	25 @ 3500~3550, 65 @ Fo±150, 70 @ Fo±1800	8.2 x 4.8 x 2.8
BNM3435-30A1	3420~3450	3.0	14	35 @ DC~2500, 3178~3208 >4000, 40 @ 2936~2966, 30@3299~3329, 20@3520~3550, 12 @ 3350~3380	8.4 x 5.6 x 2.8
BNM3437-25A1	3449~3476	2.5	1.5:1	35 @ DC~2500, 3209~3236 >4000, 40 @ 2965~2996, 30 @ 3328~3355, 15 @ 3549~3576	8.3 x 7.5 x 3
BNM3437-25B1	3449~3476	3.0	1.5:1	35 @ DC~2500, 3209~3236 >4000, 40 @ 2965~2996, 30 @ 3328~3355, 15 @ 3549~3576	8.3 x 7.5 x 3
BNM3437-25C1	3449~3476	3.0	14	35 @ DC~2475, 3184~3211, 3975~5000, 40 @ 2940~2971, 30 @ 3303~3330, 12 @ 3524~3551	8.4 x 5.6 x 2.8
BNM3450-100A1	3400~3500	2.0	2.0:1	35 @ 3150, 40 @ 2800, 30 @ 3750	9.5 x 4.75 x 3
BNM3450-100B1	3400~3500	2.0	2.0:1	15 @ 3300, 3600	8.5 x 4.6 x 3
BNM3452-28A1	3438~3466	3.0	1.5:1	40 @ 3552, 35 @ <2500, 3252,4000~5000, 40 @ 2804~2829	18.5 x 8.25 x 5.7
BNM3462-25A1	3450~3475	4.0	1.5:1	38 @ 3127~3152, 15 @ 3521~3545, 25 @ 3550~3575, 10 @ 6900~69	8.5 x 7.6 x 3.2
BNM3462-25A2	3450~3475	4.0	1.5:1	38 @ 3127~3152, 15 @ 3521~3545, 25 @ 3550~3575, 10 @ 6900~69	8.5 x 7.6 x 3.2
BNM3462-25B1	3450~3475	2.0	1.5:1	25 @ <2500, 3127~3152, 28 @ 2804~2829,10 @ 3521~3545, 6900~6950, 12.5 @ 3550~3575,23 @4000~5000	11.7 x 4.7 x 4
BNM3462-27A1	3449~3476	2.5	1.5:1	35 @ <2500, 3050~3076, >4000, 40 @ 2650~2676, 15 @ 3549~3576	8.3 x 5 x 3
BNM3462-27B1	3449~3476	2.5	1.5:1	35 @ <2500, 3209~3236, >4000, 40 @ 2965~2996, 30 @ 3328~3355, 15 @ 3549~3576	8.3 x 4.6 x 3
BNM3462-27B2	3449~3476	2.5	1.5:1	35 @ <2500, 3209~3236, >4000, 40 @ 2965~2996, 30 @ 3328~3355, 15 @ 3549~3576	8.3 x 7.5 x 3
BNM3462-27B3	3449~3476	2.5	1.5:1	35 @ <2500, 3209~3236, >4000, 40 @ 2965~2996, 30 @ 3328~3355, 15 @ 3549~3576	15 x 4.5 x 3.9
BNM3475-50A1	3450~3500	3.5	2.0:1	25 @ 3550~3600	8.2 x 4.8 x 2.8
BNM3475-50B1	3450~3500	3.5	2.0:1	25 @ 3575	8.2 x 4.8 x 2.8
BNM3480-40A1	3460~3500	4.0	1.7:1	6 @ 3448, 3512, 17 @ 3430, 3530, 35 @ 3560~3600, 42 @ 3700	15.2 x 4.6 x 4
BNM3481-31A1	3466~3497.5	3.0	1.5:1	40 @ 3581, 35 @ 3281	18.5 x 8.25 x 5.7
BNM3487-25A1	3475~3500	3.0	1.5:1	35 @ <2525, 3234~3261, >4025, 40 @ 2990~3021, 30 @ 3353~3380, 15 @ 3574~3601	8.3 x 7.5 x 3

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM3500-100A1	3450~3550	2.0	2.0:1	35 @ 3200, 40 @ 2850, 30 @ 3800	9.6 x 4.5 x 3.1
BNM3500-200A1	3400~3600	2.0	10	38 @ 3150,	6.8 x 5.7 x 2.4
BNM3500-200B1	3400~3600	2.0	2.0:1	15 @ 3250, 3750	8.3 x 4.5 x 3
BNM3500-200C1	3400~3600	4.0	2.0:1	50 @ 2850, 33 @ 3225, 30 @ 3875	15 x 4.6 x 3.9
BNM3500-200D1	3400~3600	2.5	2.0:1	8@3320, 8@3680	15x4.6x3.9
BPM3500-200A1	3400~3600	2.0	14	45 @ 3000, 45 @ 4100	22.5x10.9x6.2
BNM3505-190A1	3410~3600	4.0	2.0:1	50 @ 2850, 35 @ 3225, 30 @ 3875	15 x 5.8 x 3.85
BNM3505-190A2	3410~3600	4.0	2.0:1	50 @ 2850, 35 @ 3225, 30 @ 3875	15 x 4.6 x 3.9
BNM3515-30A1	3500~3530	4.0	2.0:1	35 @ 3400~3430	10 x 4.7 x 4
BNM3515-30B1	3500~3530	3.0	1.5:1	35 @ <2452, >3952, 40 @ 3017~3048, 30 @ 3261~3288, 28 @ 3380~3407, 15 @ 3407~3423	8.3 x 7.3 x 3
BPM3515-30A1	3500~3530	3.5	1.7:1	35 @ 3400~3430	9.7 x 4.7 x 3.7
BNM3520-42A1	3499.5~3541.5	2.5	1.5:1	35 @ <2500, >4000, 40 @ 2680~2720, 30 @ 3295~3336, 15 @ 3399~3441	8.3 x 5 x 3
BNM3520-42B1	3499.5~3541.5	2.5	1.5:1	35 @ <2500, >4000, 40 @ 3016~3061, 30 @ 3260~3300, 28 @ 3379~3420, 15 @ 3420~3441	15 x 4.3 x 3.9
BNM3524-28A1	3510~3538	3.0	1.5:1	40 @ 3424, 35 @ 3724	18.5 x 8.25 x 5.7
BNM3525-50A1	3500~3550	2.5	2.0:1	10 @ 3450, 20 @ 3700, 45 @ 4000	8.2 x 4.5 x 2.7
BNM3525-50B1	3500~3550	3.5	2.0:1	25 @ 3400~3450	8.4 x 4.6 x 3
BNM3525-50C1	3500~3550	3.5	2.0:1	25 @ 3425	8.2 x 4.5 x 3
BNM3525-50D1	3500~3550	3.5	2.0:1	35 @ <2500, >4000, 40 @ 3016~3061, 30 @ 3260~3300, 20 @ 3379~3420, 10 @ 3420~3441	8.3 x 4.5 x 3
BNM3535-30A1	3520~3550	3.0	14	35 @ <2500, 3278~3308, >4000, 40 @ 3036~3066, 30 @ 3399~3429, 20 @ 3420~3450	8.4 x 5.6 x 2.8
BNM3537-25A1	3525~3550	3.0	14	35 @ <2475, 3284~3311, 3975~5000, 40 @ 3040~3071, 30 @ 3403~3430, 15 @ 3430~3451	8.4 x 5.6 x 2.8
BNM3537-25B1	3525~3550	3.0	1.5:1	35 @ <2475, >3975, 30 @ 3284~3311, 40 @ 3040~3071, 28 @ 3403~3430, 15 @ 3430~3451	8.3 x 7.3 x 3

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM3550-100A1	3500~3600	2.0	2.0:1	35 @ 3250, 40 @ 2900, 30 @ 3850	9.5 x4.6 x3
BNM3550-100B1	3500~3600	2.0	2.0:1	15 @ 3400, 3700	8.5 x4.4 x3
BNM3550-500A1	3300~3800	1.5	12	35 @ 2300~2700 15 @ 6600~7600	11 x5.6 x3
BNM3552-28A1	3538~3566	3.0	1.5:1	40 @ 3425, 35 @ 3752	18.5 x8.25 x5.7
BNM3562-25A1	3550~3575	2.5	1.5:1	35 @ <2500, 4000~5000, 45 @ 2858~2883, 30 @ 3377~3402, 15 @ 3450~3475, 20 @ 3724~3750	8.3 x7.2 x3
BNM3562-25A2	3550~3575	2.5	1.5:1	35 @ <2500, 4000~5000, 45 @ 2858~2883, 30 @ 3377~3402, 15 @ 3450~3475, 20 @ 3724~3750	8.3 x7.6 x3
BNM3562-27A1	3549~3576	2.5	1.5:1	35 @ <2500, >4000, 40 @ 2730~2756, 30 @ 3345~3371, 15 @ 3449~3476	8.3 x5 x3
BNM3562-27B1	3549~3576	2.5	1.5:1	35 @ <2500, >4000, 40 @ 3065~3096, 30 @ 3309~3336, 28 @ 3428~3455, 15 @ 3455~3476	8.3 x5 x3
BNM3562-27B2	3549~3576	2.5	1.5:1	35 @ <2500, >4000, 40 @ 3065~3096, 30 @ 3309~3336, 28 @ 3428~3455, 15 @ 3455~3476	8.3 x7.5 x3
BNM3562-27B3	3549~3576	2.5	1.5:1	35 @ <2500, >4000, 40 @ 3065~3096, 30 @ 3309~3336, 28 @ 3428~3455, 15 @ 3455~3476	8.3 x7.2 x3
BNM3562-27B4	3549~3576	2.5	1.5:1	35 @ <2500, >4000, 40 @ 3065~3096, 30 @ 3309~3336, 28 @ 3428~3455, 15 @ 3455~3476	15 x4.5 x3.9
BNM3575-50A1	3550~3600	3.5	2.0:1	25 @ 3450~3500	8.2 x4.7 x2.8
BNM3575-50B1	3550~3600	3.5	2.0:1	25 @ 3475	8.2 x 4.7 x 2.8
BNM3575-50C1	3550~3600	3.5	2.0:1	-	8.4x4.5x3.0
BPM3575-230A1	3460~3690	3.5@Fc	15	12@Fc±135, 20@Fc±149, 30@Fc±165, 35@Fc±185, 30@Fc±365~1115	29.5x12.0x7.5
BNM3580-40A1	3560~3600	4.0	1.7:1	35 @ 3450~3500	15.2 x 4.6 x 4
BNM3581-31A1	3566~3597.5	3.0	1.5:1	40 @ 3481, 35@3781	18.5 x 8.25 x 5.7
BPM3586-25A1	3575~3600	4.0	2.0:1	30 @ 3475~3500 30 @ 3675~3700	31 x 11 x 5.5
BPM3586-25A2	3575~3600	4.0	2.0:1	30 @ 3475~3500 30 @ 3675~3700	25 x 12 x 5.5

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BNM3587-25A1	3575~3600	3.0	1.5:1	35 @ <2625, 3334~3361, >4125, 40 @ 3090~3121, 30 @ 3453~3480, 15 @ 3674~3701	8.3 x 7.5 x 3
BPM3600-200A1	3500~3700	2.0	1.5:1	45 @ 3100, 4200	22.5x10.9x6.2
BPM3600-400A1	3400~3800	2.5	15	20 @ Fc±300	22.5x9.0x6.5
BPM3600-800A1	3200~4000	2.0@Fc	2.0:1	50 @ DC~900,30@900~ 1400, 25@4600~6800	13.0x12.5x5.5
BNM3625-50A1	3600~3650	3.3	12	25 @ 3525	8.4 x 5.3 x 3
BNM3625-50B1	3600~3650	3.5	2.0:1	25 @ 3525	8.4 x 4.5 x 3
BNM3650-100A1	3600~3700	2.0	2.0:1	15 @ 3500, 3800	8.5 x 4.3 x 3
BNM3650-100B1	3600~3700	2.0	2.0:1	40 @ 3000, 35 @ 3350, 30 @ 3950	11.4 x 4.2 x 3.7
BNM3650-100C1	3600~3700	2.0	2.0:1	40 @ 3000, 33 @ 3350, 30 @ 3950	11.75 x 6.9 x 4.6
BPM3675-50A1	3650~3700	2.0	2.0:1	25 @ 3150, 4330	6.9 x 4.5 x 2.5
BNM3687-25A1	3675~3700	3.0	14	35 @ <2500, 3433~3458,4000~4500, 40 @ 3191~3216, 30 @ 3554~3579, 20 @ 3580~3600, 15 @ 3605~3630	8.4 x 5.6 x 2.8
BNM3687-25A2	3675~3700	3.0	14	35 @ <2500, 3433~3458, 4000~4500, 40 @ 3191~3216, 30 @ 3554~3579, 20 @ 3580~3600, 15 @ 3605~3630	8.6 x 7.3 x 3
BPM3687-25A1	3675~3700	4.0	2.0:1	30 @ 3575~3600, 3775~3800,	25 x 12 x 5.5
BNM3750-100A1	3700~3800	2.0	2.0:1	15 @ 3600, 3900	8.5 x 4.2 x 3
BNM3750-100B1	3700~3800	2.0	2.0:1	40 @ 3100, 35 @ 3450, 30 @ 4050	11.4 x 4.2 x 3.7
BNM3750-100C1	3700~3800	2.0	2.0:1	40 @ 3100, 33 @ 3450, 30 @ 4050	11.75 x 6.9 x 4.6
BPM3825-230A1	3710~3940	3.5@Fc	15	12@Fc±135, 20@Fc±149, 30@Fc±165, 35@Fc±185, 30@Fc±365~1115	29.5x12.0x7.5
BPM4400-800A1	4000~4800	2.0@Fc	2.0:1	50 @ DC~800,30@800~ 1400, 25@5400~8000	13.0x12.5x5.5
BPM4450-100A1	4400~4500	2.0@ Fc	1.7:1	35 @ 4250, 4650	11x10x4.8
BPM4750-500A1	4500~5000	2.0	1.5:1	40 @ 4800~6000	10.3 x 4.3 x 4

Part Number	Frequency Range (MHz)	I.L. in BW (dB)(max)	VSWR or R.L.	Attenuation (dB)(min) @ MHz	Dimension (L x W x H)(mm)
BPM5100-600A1	4800~5400	2.0@Fc	2.0:1	40@DC~3600, 30@3600~4200, 25@6000~9200	13.0x12.5x5.5
BNM5220-140A1 (BPF571)	5150~5290	2.5	13	30 @ 5540~5850	8.6x5.5x3.9
BNM5250-200A1 (BPF0561)	5150~5350	2.0	2.0:1	20 @ 4800, 15 @ 4875, 5 @ 5625	4.4 x 4.7 x 1.95
BNM5250-200B1	5150~5350	3.0	2.0:1	20 @ 4800, 15 @ 4875, 5 @ 5625	5.8 x 5 x 2
BNM5250-200C1	5150~5350	3.0	2.0:1	35 @ 4100, 20 @ 4800, 15 @ 4875, 5 @ 5625	8.5 x 4.9 x 3
BNM5250-200D1 (BPF0563)	5150~5350	2.5	12	45 @ 5640~5660	8.2x4.2x3.0
BNM5500-500A1	5250~5750	3.0	15	30 @ 4875, 6125	7.5x5.15x2.1
BNM5500-750A1	5125~5875	3.0	15	18 @ 4875, 6125	7.5x5.15x2.1
BNM5550-600A1	5250~5850	2.0	1.7:1	48 @ 4400~5000, 40 @ 6400~10000	26 x 10.2 x 4.1
BNM5660-380A1	5470~5850	1.8	10	30 @ 4940~4990	3.8 x 6.8 x 2.8
BNM5675-120A1	5615~5735	2.8	2.0:1	35 @ 5250, 25 @ 5375	8.5 x 4.9 x 3
BNM5697-305A1 (BPF572)	5545~5850	2.5	13	35 @ 5150, 25@5375	8.5x4.9x3.0
BPM5700-600A1	5400~6000	2.0@Fc	2.0:1	40@DC~3800, 35@3800~4600, 20@6400~10200	13.0x12.5x5.5
BPM5775-50A1	5750~5800	2.5	14.0	30 @ 5350	10.6 x 4 x 2.5
BNM5787-125A1	5725~5850	1.8	2.0:1	20 @ 5350, 10 @ 5475	8.3 x 4.2 x 2.8
BNM5787-125B1	5725~5850	2.8	2.0:1	35 @ 5350, 25 @ 5475	8.5 x 4.5 x 2.9
BNM5800-100A1	5750~5850	2.0	2.0:1	25 @ 5425, 10 @ 6175	4.4 x 3.9 x 1.95
BNM5800-150A1	5725~5875	2.0	2.0:1	15 @ 5425, 5 @ 6175	4.4 x 4.1 x 1.95
BPM5800-150A1	5725~5875	1.5	2.0:1	45@ 5400, 30 @ 6500	-
BNM5800-200A1	5700~5900	3.0	2.0:1	20 @ 5350, 15 @ 5425, 5 @ 6175	8.5 x 4.5 x 3
BNM5825-200A1 (BPF0562)	5725~5925	2.0	2.0:1	35@4559	4.5x3.85x1.7
BNM5825-200B1 (BPF0564)	5725~5925	2.5	12	45@5415~5435	8.2x3.85x3.0
BPM5880-100A1	5830~5930	1.5	2.0:1	25@5505, 10@6255	4.4x3.95x1.95