

| Part Number | Passband Frequency (MHz) | I.L. in BW (dB)(max) | VSWR or R.L. | Attenuation (dB)(min) | Dimension (L x W x H)(mm) |
|---------------------|------------------------------|----------------------|--------------|----------------------------------------------------|----------------------------------|
| DTL14-26-14A1 | L: DC ~ 14 H: 26 ~ 200 | 1.5 1.0 | 15 | 20 @ 18MHz, 40 @ 20MHz 50 @ 22.5MHz, 60 @ 24MHz | 25.4 x 25.4 x 10.2 (Pin Type) |
| DPL42-54-37A1 | L: 5 ~ 42 H: 54 ~ 860 | 2.5 | 15 | 60 @ 54 ~ 90MHz | 20 x 20 x 10 (SMD Type) |
| DCL108-147-108A1 | L: DC ~ 108 H: 147 ~ 500 | 1.0 | 15 | 50 @ 147 ~ 500MHz 50 @ DC ~ 108 MHz | 98 x 51 x 28 (N female) |
| DCL240-370-240A1 | L: DC ~ 240 H: 370 ~ 1000 | 0.8 | 15 | 50 @ DC ~ 370 ~ 1000MHz 50 @ DC ~ 240MHz | 98 x 51 x 28 (N female) |
| DCL446-460-226A1 | L: 220 ~ 446 | 1.0 | 15 | 30 @ 100 ~ 160MHz 30 @ 600 ~ 800MHz | 110 x 80 x 30 (N female) |
| | H: 460 ~ 800 | | | 20 @ 200 ~ 400MHz 30 @ 1000 ~ 1200MHz | |
| DPL495-540-110A1 | L: 385 ~ 495 | 2.5 | 14 | 10 @ 540, 495MHz | 65 x 23 x 13.3 (SMD Type) |
| | H: 540 ~ 680 | | | | |
| DCL500-800-500A1 | L: DC ~ 500 | 0.8 | 15 | 50 @ 800 ~ 2200MHz | 98 x 51 x 28 (N female) |
| | H: 800 ~ 2200 | | | 50 @ DC ~ 500MHz | |
| DPL595-620-110A1 | L: 485 ~ 595 | 2.5 | 14 | 10 @ 620 MHz / 595 MHz | 65 x 23 x 13.3 (SMD Type) |
| | H: 620 ~ 760 | | | | |
| DPL892-1850-136A1 | L: 824 ~ 960 | 1.5 | 15 | 50 @ 1710 ~ 1990MHz | 41 x 23 x 6 (SMD Type) |
| | H: 1710 ~ 1990 | | | 60 @ 824 ~ 960MHz | |
| DPL960-1710-160A1 | L: 800 ~ 960 | 1.0 | 14 | 25 @ 800 ~ 960MHz | 16 x 10 x 5.5 (SMD Type) |
| | H: 1710 ~ 2500 | | | 25 @ 1710 ~ 2500MHz | |
| DCL1000-1700-1000A1 | L: DC ~ 1000 | 0.8 | 15 | 50 @ 1700 ~ 2170MHz | 98 x 51 x 28 (N female) |
| | H: 1700 ~ 2170 | | | 50 @ DC ~ 1000MHz | |
| DPL1000-1710-200A1 | L: 800 ~ 1000 | 0.7 | 15 | 60 @ 800 ~ 1000MHz | 98 x 51 x 28 (SMD Type) |
| | H: 1710 ~ 2200 | | | 60 @ 1710 ~ 2200MHz | |
| DCL1880-1920-1080A1 | L: 800 ~ 1880 | 2.0 | 12 | 50 @ 1920 ~ 2170MHz | 100 x 80 x 30 (N female) |
| | H: 1920 ~ 2170 | | | 50 @ 800 ~ 1880MHz | |

| Part Number | Passband Frequency (MHz) | I.L. in BW (dB)(max) | VSWR or R.L. | Attenuation (dB)(min) | Dimension (L x W x H)(mm) |
|---------------------|--------------------------|----------------------|--------------|--------------------------|------------------------------|
| DCL2000-2400-1200A1 | L: 800 ~ 2000 | 1.5 | 12 | 75 @ 2400 ~ 2500MHz | 80 x 60 x 30 (N female) |
| | H: 2400 ~ 2500 | | | 75 @ 800 ~ 2000MHz | |
| MPL-000001A1 | P1: 46 ~ 53 | 3.0@49.5MHz | 1.5:1 | 50 @1~26.5, 69~500MHz | 33.0 x 25.4 x 6.9 |
| | P2: 53 ~ 68.5 | 3.0@60.75MHz | | 50 @1~34.5, 79.5~500MHz | |
| | P3: 68.5 ~ 88 | 3.0@78.25MHz | | 50 @1~44, 103~500MHz | |
| | P4: 88 ~ 94 | 3.0@91MHz | | 50 @1~47, 132~500MHz | |
| MPL-000005A1 | P1: 67 ~ 174 | 1.5 | 14 | 35 @ other bands | 45 x 26 x 20 (SMD Type) |
| | P2: 350 ~ 512 | 2.0 | | 20 @ 1710 ~ 2700MHz | |
| | P3: 698 ~ 960 | 2.0 | | 20 @ 1710 ~ 2700MHz | |
| MPL-000002A1 | P1: 75 ~ 89 | 3.0@82MHz | 1.5:1 | 50 @1~44.5, 112.5~500MHz | 33.0 x 25.4 x 6.9 |
| | P2: 89 ~ 106 | 3.0@97.5MHz | | 50 @1~53, 133.5~500MHz | |
| | P3: 106 ~ 126 | 3.0@116MHz | | 50 @1~63, 159~500MHz | |
| | P4: 126 ~ 150 | 3.0@138MHz | | 50 @1~75, 189~500MHz | |
| MPL-000003A1 | P1: 100 ~ 130 | 3.0@115MHz | 1.5:1 | 50 @1~65, 150~500MHz | 33.0 x 25.4 x 6.9 |
| | P2: 130 ~ 140 | 3.0@135MHz | | 50 @1~70, 195~500MHz | |
| | P3: 140 ~ 172 | 3.0@156MHz | | 50 @1~86, 210~500MHz | |
| | P4: 172 ~ 180 | 3.0@176MHz | | 50 @1~90, 258~500MHz | |
| MCL-000001A1 | P1: 146 ~ 174 | 3.0 | 14 | 70 at each band | 140 x 100 x 23 (N female) |
| | P2: 380 ~ 415 | | | | |
| | P3: 890 ~ 960 | | | | |
| | P4: 1710 ~ 1880 | | | | |

| Part Number | Passband Frequency (MHz) | I.L. in BW (dB)(max) | VSWR or R.L. | Attenuation (dB)(min) | Dimension (L x W x H)(mm) |
|--------------|--------------------------|----------------------|--------------|-----------------------|-----------------------------|
| MPL-000004A1 | P1: 150 ~ 178 | 3.0@164MHz z | 1.5:1 | 50 @1~89, 225~700MHz | 33.0 x 25.4 x 6.9 |
| | P2: 178 ~ 212 | 3.0@195MHz z | | 50 @1~106, 227~700MHz | |
| | P3: 212 ~ 252 | 3.0@232MHz z | | 50 @1~126, 318~700MHz | |
| | P4: 252 ~ 300 | 3.0@276MHz z | | 50 @1~150, 378~700MHz | |
| MPL-000006A1 | P1: 380 ~ 490 | 2.0 | 15 | 20 @ P2, P3 | 45 x 28 x 8.0 (SMD Type) |
| | P2: 800 ~ 960 | | | 20 @ P1, 35 @ P3 | |
| | P3: 1700 ~ 2200 | | | 35 @ P1, P2 | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |