

Part Number	Passband Frequency (MHz)	I.L. in BW (dB)(max)	VSWR or R.L in BW	Attenuation (dB)(min)	Dimension (L x W x H)(mm)
HPL20-80A1	20 - 100	1.5	15	40 @ 10MHz	25.4 x 12.7 x 6.7
HPL 28-572A1	28 - 600	1.0	14	40 @ 15MHz	25.4 x 12.7 x 6.7
HPL56-943A1	56 - 1000	1.0	14	40 @ 30MHz	25.4 x 12.7 x 6.7
HPL225-775A1	225 - 1000	1.5	15	30 @ 30-110MHz	47 x 1S x 7.5
HCL450-550A1	450~1000	1.0	15	20 @ 401 MHz	36.8 x14.0 x10.2
HPL500-1500A1	500~2000	1.0	1.5:1	60 @ DC~400 MHz	25.4 x 12.7 x 6.7
HPL585-775A1	585 - 1500	1.5	15	20 @ 540MHz, 60 @ 480MHz	25.4 x 12.7 x 6.7
HPL550-450A1	550 - 1000	1.0	15	60 @ DC-250MHz	25.4 x 12.7 x 6.7
HPL1000-1000A1	1000 - 2000	1.5	15	40 @ 800MHz	25.4 x 12.7 x 6.7
HCL1600-11150A1	1600 - 12750	0.5	14	40 @ 600MHz	31.8 x 11.2 x 10.2
HPL1350-1050-X-LL	1350 - 2400	1.2	15	25 @ DC- 1000MHz	25.4 x 12.7 x 6.7
HPL2360-880A1	1920 - 2800	1.5	15	12 @ DC - 1 78SMHz	8.2 x 7.8 x 2.8
HPL2550-900A1	2100 - 3000	1.5	15	18 @ DC - 1880MHz	8.2 x 7.8 x 2.8